

Fan Speed Controllers VFD

For prices please contact us

Series No.(RM5G)	4001	4002	4003	4005	4007	4010	4015	4020	4025	4030	4040
Rated power of the motor(HP/KW)	1/ 0.75	2/ 1.5	3/ 2.2	5/ 3.7	7.5/ 5.5	10/ 7.5	15/ 11	20/ 15	25/ 18.5	30/ 22	40/ 30
Rated continuous output power(KVA)	1.9	3.3	4	7	10	14	18	23	30	34	46
Rated continuous output current(A)	2.5	4	6	9	14	18	24	30	39	45	61
Rated output voltage	3 ϕ 380 ~ 480V										
Range of output frequency(Hz)	0.01 ~ 400Hz										
Power source(ϕ ,V,Hz)	3 ϕ 380 ~ 480V 50/60Hz										
Tolerance of power source voltage	332V ~ 528V 50/60Hz										
Tolerance of frequency fluctuation	\pm 5%										
Construction protected	IP20										



Series No.(RM5G)	4050	4060	4075	4100	4125	4150	4175	4200	4250	4300	4420	4500
Rated power of the motor(HP/KW)	50/ 37	60/ 45	75/ 55	100/ 75	125/ 90	150/ 100	175/ 132	200/ 160	250/ 200	300/ 220	420/ 315	500/ 370
Rated continuous output power(KVA)	56	66	84	104	134	165	193	232	287	316	445	534
Rated continuous output current(A)	73	87	110	150	176	210	253	304	377	415	585	700
Rated output voltage	3 ϕ 380 ~ 480V											
Range of output frequency(Hz)	0.01 ~ 400Hz											
Power source(ϕ ,V,Hz)	3 ϕ 380 ~ 480V 50/60Hz											
Tolerance of power source voltage	332V ~ 528V 50/60Hz											
Tolerance of frequency fluctuation	\pm 5%											
Construction protected	IP20 IP00 (IP20 OPTION)											

For prices please contact us

For more information:

Telephone: 0118 950 0606
email: sales@thermagroup.com

Fax: 0118 956 0039
web site: www.thermagroup.com

All prices exclude VAT